



## At a Glance

Ethernet, SFP, Dual SIM Single Radio LTE (Active/Standby), xDSL

Four x 1 Gbit LANs; up to Eight Wireless SSIDs

PCI DSS Certified

# Mako 6600-M

Fast and flexible, scalable and secure.

## Engineered to Perform

The 6600-M continues Mako's legacy of design innovation, building on the highly secure 6500 platform and incorporating new features that deliver faster, more flexible business networking. With a sealed, tamper-proof case, no moving parts and high heat tolerance, the 6600-M stands up to tough network environments like petroleum, QSRs and retail. The 6600 series adds a dual-SIM LTE module, higher transfer speeds, more efficient VPN performance and an SFP port, allowing for multi-WAN configurations (SD-WAN) while retaining four physically-segmented LAN ports.

### PCI DSS CERTIFIED

The entire Mako System—including the 6600-M appliance, our wireless networking technology, the Central Management System and our onboard software—is PCI DSS certified from end-to-end, providing peace of mind and security for businesses that accept credit cards. Mako's PCI-certified wireless networking technology is a perfect fit for wireless and tablet-based POS systems. When using Mako's PCI-certified network configuration templates, Mako's PCI reach is unsurpassed.

### CENTRALIZED LOGGING/REPORTING

Using a patented communications protocol, the Mako 6600-M securely connects to the Central Management System (CMS), providing data that is used to generate easy-to-understand graphical reports. Real-time information about the network, including cellular and broadband data use by site, user and timeframe, intrusion attempts, Internet traffic records, estate-wide network status and much more is available to authorized users 24x7.

### USER-DEFINED WAN FAILOVER

The Mako 6600-M's WAN interfaces can be configured to fail over from one another in the event of failure through to seamless connectivity that won't even drop a live voice call should a network connection drop. These fast, flexible failover options offer businesses continuity in the case of unexpected interruptions while also providing high availability at a business-friendly cost. Combine fixed-line connections with single or dual SIM LTE in any connection order or failover pattern your business needs.

### EMBEDDED WIRELESS

The Mako 6600-M features single or dual-band wireless on b/g/n and ac standards for customer hotspots or general business use, supporting up to eight wireless SSIDs per appliance.

### MAKO VPN CLOUD MAKES CREATING VIRTUAL PRIVATE NETWORKS EASY

Connect retail or remote locations to head offices, data centers or third-party vendors easily. Choose the amount of resiliency and redundancy your business needs. Mako VPN Cloud supports circuit, hardware and geographic redundancy, allowing your Mako 6600-M appliance to deliver fast, reliable VPN connectivity across any combination of broadband circuit types. Remote locations connected by Mako appliances can be linked in seconds by three easy mouse clicks in the CMS, all without requiring static IP addresses. Each Mako 6600-M can simultaneously link up to 50 external VPNs

### SIMPLE TROUBLESHOOTING

In addition to CMS troubleshooting diagnostic tools, a color-coded LED panel on the Mako 6600-M provides Internet and network connection information at a glance. For non-technical users, this makes it easy to quickly diagnose network issues.

### FLEXIBLE CONNECTION OPTIONS

Mako 6600-M appliances provide WAN connectivity via LTE, Ethernet, fiber or xDSL at up to 1Gbit transfer speeds. No matter what technology your business uses to connect to the Internet, Mako can support and protect it.

### QUICK AND EASY TO DEPLOY

Like all Mako appliances, the 6600-M allows for zero touch deployment by automatically receiving site-specific configuration information from the Mako CMS via the cloud. Remote sites can get up and running quickly and easily, even when running on LTE-only broadband.



## Technical Specifications

### Hardware

WAN Interface, Ethernet	1 x Ethernet RJ45 10/100/1000 Mbps port. Auto crossover.
WAN Interface, SFP	1x SFP (usable as LAN or WAN).
WAN Interface, Cellular	LTE/3G Cellular Interface, Dual SIM, Single Radio LTE (Active/Standby)
WAN Interfaces xDSL (optional)	1 x RJ11 ITU G.992 port.
LAN Interfaces	4 x Ethernet RJ45 10/100/1000 Mbps ports. Auto crossover.
Power Supply	External 100 or 240VAC Input (50 or 60Hz) 12VDC output
USB Port	For support functions (i.e. manual configuration).
Chassis Dimensions	8.58 x 8.58 x 1.57 inches 218 x 218 x 40 mm (L x W x H)
Operating Temperature	41° F to 104° F 5° C to 40° C
Humidity	10% to 90% relative, non-condensing
Hardware VPN Encryption	Supported
Power Consumption	48W - Maximum

### Cellular Protocols

US/EU	
LTE	Bands (1,2,3,4,5,7,8,12,13,20,25,26,29,30,41)
UMTS/HSPA(+)	Bands (1,2,3,4,5,8)
Modem	MC7455 (USA/EU)
AUS/NZ/UK	
LTE	Bands (1,3,5,7,8,18,19,21,28,38,39,40,41)
UMTS/HSPA(+)	Bands (1,5,6,8,19)
Modem	MC7430 (APAC)

### Wi-Fi

Channels	2.4, 5 GHz, four SSIDs supported per radio (model-dependent)
Supported Standards	802.11 b/g/n/ac
Bandwidth	Up to 867Mbps
Security	WPA2 Personal / WPA2 Enterprise
Frequencies	<b>W1 variant:</b> 2.4GHz: 2.412 ~ 2.484 GHz / 5.4GHz: 5.180 ~ 5.825 GHz (region-dependent) <b>W2 variant:</b> (adds additional 2.4GHz range) 2.4GHz: 2.412 ~ 2.472 GHz plus 2.4GHz: 2.412 ~ 2.484 GHz / 5GHz: 5.180 ~ 5.825 GHz (all ranges are region-dependent)
Other	Integrated access point scanning Wireless Multimedia (WMM) QoS
Output Power	2.4GHz (max 21dBm) 5GHz (max 20dBm) per chain

### Compliance

Environmental	Lead-free and RoHS compliant
Firewall	PCI DSS, Verifone (MNSP Program), GDPR

### Model Variations

6600-M-W1-LTE	Single-band wireless (802.11 b/g/n/ac) + LTE WAN
6600-M-W2-LTE	Dual-band wireless (802.11 b/g/n/ac) + LTE WAN

### Contact Mako Networks

+1 888 777 5413

ussales@makonetworks.com

makonetworks.com

